

TYPE A Male Camlock x Female BSP

ALUMINIUM

Part Number	Product Size
654-A1020	3/4"
654-A1025	1"
654-A1032	1¼"
654-A1038	1½"
654-A1050	2"
654-A1065	2½"
654-A1075	3"
654-A1100	4"
654-A1125	5"
654-A1150	6"
654-A1200	8"



TYPE B Female Camlock x Male BSP

ALUMINIUM

Part Number	Product Size
654-B3020	3/4"
654-B3025	1"
654-B3032	1¼"
654-B3038	1½"
654-B3050	2"
654-B3065	2½"
654-B3075	3"
654-B3100	4"
654-B3125	5"
654-B3150	6"
654-B3200	8"



Pressure Rating: Based on ambient Temperature 20°C

3/4" - 2"	250psi
2½"	150psi
3"	125psi
4"	100psi
5" - 6"	75psi
8"	50psi

TYPE C Female Camlock x Hosetail

ALUMINIUM

Part Number	Product Size
654-C9020	3/4"
654-C9025	1"
654-C9032	1¼"
654-C9038	1½"
654-C9050	2"
654-C9065	2½"
654-C9075	3"
654-C9100	4"
654-C9125	5"
654-C9150	6"
654-C9200	8"



TYPE D Female Camlock x Female BSP

ALUMINIUM

Part Number	Product Size
654-D2020	3/4"
654-D2025	1"
654-D2032	1¼"
654-D2038	1½"
654-D2050	2"
654-D2065	2½"
654-D2075	3"
654-D2100	4"
654-D2125	5"
654-D2150	6"
654-D2200	8"



Pressure Rating: Based on ambient Temperature 20°C

3/4" - 2"	250psi
2½"	150psi
3"	125psi
4"	100psi
5" - 6"	75psi
8"	50psi

TYPE E Male Camlock x Hosetail

ALUMINIUM

Part Number	Product Size
654-E2020	3/4"
654-E2025	1"
654-E2032	1¼"
654-E2038	1½"
654-E2050	2"
654-E2065	2½"
654-E2075	3"
654-E2100	4"
654-E2125	5"
654-E2150	6"
654-E2200	8"



TYPE F Male Camlock x Male BSP

ALUMINIUM

Part Number	Product Size
654-F1020	3/4"
654-F1025	1"
654-F1032	1¼"
654-F1038	1½"
654-F1050	2"
654-F1065	2½"
654-F1075	3"
654-F1100	4"
654-F1125	5"
654-F1150	6"
654-F1150	8"



Pressure Rating: Based on ambient Temperature 20°C

3/4" - 2"	250psi
2½"	150psi
3"	125psi
4"	100psi
5" - 6"	75psi
8"	50psi

TYPE DC Dust Cap

ALUMINIUM

Part Number	Product Size
654-DC020	3/4"
654-DC025	1"
654-DC032	1¼"
654-DC038	1½"
654-DC050	2"
654-DC065	2½"
654-DC075	3"
654-DC100	4"
654-DC125	5"
654-DC150	6"
654-DC200	8"



TYPE DP Dust Plug

ALUMINIUM

Part Number	Product Size
654-DP020	3/4"
654-DP025	1"
654-DP032	1¼"
654-DP038	1½"
654-DP050	2"
654-DP065	2½"
654-DP075	3"
654-DP100	4"
654-DP125	5"
654-DP150	6"
654-DP200	8"



Pressure Rating: Based on ambient Temperature 20°C

3/4" - 2"	250psi
2½"	150psi
3"	125psi
4"	100psi
5" - 6"	75psi
8"	50psi